

पेटेंट कार्यालय
शासकीय जर्नल

OFFICIAL JOURNAL
OF
THE PATENT OFFICE

निर्गमन सं. 46/2017
ISSUE NO. 46/2017

शुक्रवार
FRIDAY

दिनांक: 17/11/2017
DATE: 17/11/2017

पेटेंट कार्यालय का एक प्रकाशन
PUBLICATION OF THE PATENT OFFICE

(12) PATENT APPLICATION PUBLICATION

(21) Application No.201741039638 A

(19) INDIA

(22) Date of filing of Application :07/11/2017

(43) Publication Date : 17/11/2017

(54) Title of the invention : ADVANCED WHEEL SUSPENSION SYSTEM

(51) International classification	:B60G 11/14	(71)Name of Applicant : 1)CMR COLLEGE OF ENGINEERING & TECHNOLOGY Address of Applicant :CMR College of Engineering & Technology, Kandlakoya, Medchal road, Hyderabad 501401, Telangana, India. Telangana India
(31) Priority Document No	:NA	2)RAJ VENKAT SAI SADU
(32) Priority Date	:NA	3)SUMANTH V
(33) Name of priority country	:NA	4)DR. MERUGU SURESH
(86) International Application No	:NA	5)MR. P. RAVEENDRA BABU
Filing Date	:NA	6)DR. P. RAVI KUMAR
(87) International Publication No	: NA	(72)Name of Inventor :
(61) Patent of Addition to Application Number	:NA	1)RAJ VENKAT SAI SADU
Filing Date	:NA	2)SUMANTH V
(62) Divisional to Application Number	:NA	3)DR. MERUGU SURESH
Filing Date	:NA	4)MR. P. RAVEENDRA BABU
		5)DR. P. RAVI KUMAR

(57) Abstract :

ABSTRACT Exemplary embodiments of the present disclosure are directed towards an advanced wheel suspension system. The system includes atleast two suspension members, a hub and a rim, whereby the suspension further includes atleast two coils and atleast one coil for compression and the other atleast one coil for expansion of suspension. The atleast two suspension members of the wheel is resilient to absorb impact force to the conveyance without the use of pneumatic or hydraulic constituents and can maintain the interval when tension is up to threshold value. The atleast two suspension members can compress or elongate when tension is beyond the threshold value and retrieve to initial state when impact force reduces to threshold value. It is suitable for conveyance like bicycle wheels, wheelchair and self-propelled vehicles. The vehicle with these wheels cannot jerk or skid at jumpstart or braking.

No. of Pages : 12 No. of Claims : 5